

T-1/R

MODULAR SPEAKER



Outfitted with reference-grade components, the T-1/R takes the performance of the T-1 to the next level. The T-1/R inherits all the benefits of the T-1s driver configuration, with increased audio quality and higher power handling. With exceptional fidelity and detail, the T-1/R is designed for the discriminating audio enthusiast who takes a no-compromise attitude with his or her audio system. This model is only available in custom veneer finishes.

R B HASSING
TM



REDEFINING THE WAY YOU EXPERIENCE SOUND.™

382 Marshall Way, Layton, Utah • USA • 84041 • Toll Free: (800) 543-2205 • Fax: (801) 543-3300 • www.rbhsound.com
It is RBH Sound policy to continuously incorporate improvements into products; all specifications are subject to change without notice. Copyright © 2010 RBH Sound. All Rights Reserved.

SPECIFICATIONS

MODEL NAME:

T-1/R

SYSTEM TYPE:

Modular Speaker

SERIES

Signature Reference Series T Systems

FREQUENCY RESPONSE

45Hz — 20kHz ± 3dB

SENSITIVITY

91dB (2.83 Volts @ 1 Meter)

RECOMMENDED POWER

100-500 Watts

DRIVE UNITS

(4) 6½" (165mm) Aluminum Woofers

(3) 1.1" (28mm) Silk Dome Tweeters

CROSSOVER FREQUENCY

2,500 Hz

CROSSOVER

24dB/Octave

IMPEDANCE

4 Ohms

CABINET

Custom Veneers Only Choose From 30 Different Real Wood Finishes

GRILLE

Black Cloth

DIMENSIONS

13¼" W x 30" H x 18" D

(336mm W x 762mm H x 457mm D)

WEIGHT

75 lbs. (34.02 kg)

WARRANTY

5 Years*

*Warranted for 5 (five) years from date of purchase to be free from defects and workmanship. For more information see your RBH dealer.



R B HASSING




High Performance Home Audio
Redefining the Way You Experience Sound™

T-1/R


MODULAR SPEAKER

DIMENSIONS




CONFIGURATIONS


The mid-range and bass drive units of the T System are of the highest quality and feature cutting-edge aluminum cone technology. The woofers and tweeters are arranged in a dispersion-averaging alignment that focuses the sound at the listening position for unbelievable imaging. Working in harmony, all drive units are governed by an extensive filter network to convey the sonic realism you'd expect from this reference-grade speaker system.




T-1 or T-1/R




T-2N or T-2N/R



T-2P or T-2P/R



T-3N or T-3N/R



T-3P or T-3P/R

T-2N or T-2N/R:	2 each T-1 or T-1/R Modular Speakers 2 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 2 sets of T-Module Clamps 2 sets of T-Module Feet	T-3N or T-3N/R:	2 each T-1 or T-1/R Modular Speakers 4 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 4 sets of T-Module Clamps 2 sets of T-Module Feet
T-2P or T-2P/R:	2 each T-1 or T-1/R Modular Speakers 2 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 2 each SA-400 Subwoofer Amplifiers 2 sets of T-Module Clamps 2 sets of T-Module Feet	T-3P or T-3P/R:	2 each T-1 or T-1/R Modular Speakers 4 each 1010-SEN or 1010-SEN/R Non-powered Subwoofers 4 each SA-400 Subwoofer Amplifiers 4 sets of T-Module Clamps 2 sets of T-Module Feet

Specifications are subject to change. For the most current information visit us online at www.rbhsound.com.